




Defy the Elements

Permanently attached Vortex® valve automatically adjusts air pressure without letting in water.

Add the security of your own padlock to unbreakable, molded-in hasps.

> The unique hinges with feet hold fast under impact and create a flat surface for upright stability.

> > Double-layered, soft-grip handles combine strenath with long lasting comfort.



Molded-in stacking ribs provide no-slip stability for multiple case stacking during storage or transport.

Storm Cases are designed to transport and protect your valuables even under the most adverse conditions.



Dimensions: Exterior Dimensions (LxWxH) 11.8 x 9.8 x 7.7 in. 299 x 248 x 195 mm

Interior Dimensions* (LxWxH) 9.5 x 7.5 x 7.25 in. 241 x 191 x 184 mm
*Total height shown; includes lid depth of 1.5 inches.

WEIGHT (EMPTY): 3.3 lbs/1.5 kg

FFATURES:

Two Press & Pull Latches Double-layered, Soft-grip Handle Two Padlockable Hasps Vortex® Valve Flush Powerful Hinges Meets Carry-on Regulations Lightweight Strong HPX® Resin Watertight Guaranteed For Life

COLORS:

Black, Yellow, Gray, Orange, or Olive Drab

INTERIOR FOAM: Multilayer Cubed Foam or No Foam

STANDARD OPTIONS: Bezel Kit Manual Purge Valve Lid Stavs Lock Shoulder Strap

CUSTOMIZED OPTIONS:

Custom Foam Label (no label, custom labels) **Custom Colors** Molded-in 3D Graphics Foil Stamping



Storm Caso Advantago





















Storm outpowers the competition.

Competition

reutore	Competition	Storin Case	Storm Case Advantage
Case Material	Polypropylene or ABS	HPX® High Performance Resin	 Better Impact Resistance Guaranteed for Life Lightweight
Latches	Narrow "Knuckle Buster" DesignMay Pop Open When Dropped	Press & Pull Operation with Extra Strength Wide DesignWon't Pop Open When Dropped	 Pain Free Latch Operation That's Twice as Strong More Secure Case Closure
Purge Valve	Manual Pressure Adjustment Valve Screws Out (Could get lost)	● Vortex® Valve ● Valve Won't Fall Out	 Automatically Adjusts to Changing Environments No Lost Valves
Carry Handle	Hard, One-piece Construction or Thinly Padded with Harder Rubber	Durable Inside Core with Soft Overlay	More Comfortable to Carry
Nameplate Area	Adhesive Labels	Adhesive LabelsCustom 3-D Logo Option	Easy CustomizationPermanent, Molded-In Logos That Can't Fall Off
Cubed Foam System	Single Layer of Cubed Foam	Multilayer Cubed Foam	 Highly Customizable to Your Individual Needs
Panel Mount System	Plastic Frame Screwed to Interior, Variable Height	 Extruded Aluminum Rails with Molded Corner Pieces Watertight, Sealed Rivet Attachment for Custom Fit 	 Stronger Panel Mount Construction Permanent, More Secure Panel Attachment

Storm Caso

Life is an endurance test—so each Storm Case passes extreme testing requirements.

Test	Specifications Met	Description	
Drop Test	FED-STD-101C, Method 5007.1, Paragraph 6.3, Procedure A, Level A. Tests are superseded and concurrent with ASTM B 4169, DC-18, Assurance Level 1, Schedule A.	A series of 26 drops, one on each corner, edge, and face, from 19" to 30", depending on the gross weight of the case, with loads of 15 lbs to 70 lbs (depending on case size).	
Falling Dart Impact	ATA 300, Category I, "General Requirements for Category I and II Reusable Containers"	A dart weighing 13.22 lbs with a 1.25" hemispherical end was dropped on each case from 19.68".	
Vibration (loose cargo)	FED-STD-101C, Method 5019 Tests are superseded and concurrent with ASTM B 4169, DC-18, Assurance Level 1, Schedule F.	Each case was vibrated for 20 minutes per axis. 1-inch peak to peak at around 4.75 Hz.	
Vibration (sweep)	ATA 300 (Jan 15/96) states in Appendix II, B.4 This test also exceeds the specifications listed in MIL-STD-648C and may also fulfill ISO 8318 and ISO 2247.	Vibration Test for Category I containers — Vibration tests shall be conducted on Category I containers in accordance with ASTM Designation D-999, Procedure B, within the range of 5 to 50 cycles per second for a period of not less than two (2) hours.	
Simulated Rainfall	MIL-STD-810F, Method 506.4, Procedure II of 4.1.2 FED-STD-101C Method 5009.1, Sec 6.7.1 Tests are superseded and concurrent with ASTM B 4169, DC-18, Assurance Level 1, Schedule H.	Four inches of rain per hour for 20 minutes each side. This was followed by a 4-hour test at 4" per hour on the top. Both tests saw the case heated to 18°F higher than the water temp.	
Immersion	MIL-STD-810F, Method 512.4	A 1-meter (3.281 feet) immersion for 1 hour with the case being heated to 40°F higher than the water temperature.	

Storm Cases are more than just watertight, padlockable and **made in the USA**, they're also Guaranteed for Life. Interested in Harnessing the Power of a Storm? Call us at **800.542.7344** or visit us online at **StormCase.com**.



Hardigg® Cases • 147 North Main Street, South Deerfield, MA 01373 • 800.542.7344 • StormCase.com

Hardigg® Europe • Unit 4, Brookfield Industrial Estate, Leacon Road, Ashford, Kent TN23 4TU, UK • +44(0)1233 895895 • HardiggEurope.com Hardigg® Canada • 360 Boul. Du Seminaire, N. Local 20, St-Jean-sur-Richelieu, QC, Canada J3B 5L1 • 450.348.2753 • Hardigg.com



Made in the USA Part # \$13693 - Rev. A