





Permanently attached Vortex® valve automatically adjusts air pressure without letting in water.



Add the security of your own padlock to unbreakable, molded-in hasps.



Telescoping handles & rugged in-line wheels make transport fast and comfortable



Double-layered, soft-grip handles combine strength with long lasting comfort.



will outlast every situation.


Storm Cases are designed to transport and protect your valuables even under the most











CUSTOMIZED OPTIONS: Custom Foam

Utility Organizer

iM3075

Dimensions:

WEIGHT (EMPTY):

31.5 lbs/14.3 kg

Seven Press & Pull Latches

Two Padlockable Hasps

FEATURES:

In-line Wheels

Watertiaht

Dustproof Guaranteed for Life

COLORS: Black or Olive Drab

OPTIONS: Manual Purge Valve

Lid Stays Padded Divider Set

Lock

INTERIOR FOAM:

Multilayer Cubed Foam or No Foam

Telescoping Handle Vortex® Valve Flush Powerful Hinges Lightweight Rugged HPX® Resin

Exterior Dimensions (LxWxH) 33 3 x 24 4 x 19 3 in 846 x 620 x 490 mm

Interior Dimensions* (LxWxH) 29.8 x 20.8 x 17.8 in. 757 x 528 x 452 mm

* Total height shown; includes lid depth of four inches

Four Double-layered, Soft-grip Handles

Label (no label, custom labels) **Custom Colors** Molded-in 3D Graphics Foil Stampina



PRM CASE Defy the Elements



adverse conditions.





Storm outpowers the competition.

	ano			
Feature	Competition	Storm Case	Storm Case Advantage	
Case Material	Polypropylene or ABS	HPX® High Performance Resin	 Better Impact Resistance Guaranteed for Life Lightweight 	
Latches	Narrow "Knuckle Buster" Design May Pop Open When Dropped	 Press & Pull Operation with Extra Strength Wide Design Won't Pop Open When Dropped 	 Pain Free Latch Operation That's Twice as Strong More Secure Case Closure 	
Purge Valve	Manual Pressure Adjustment Valve Screws Out (Could get lost)	Vortex® Valve Valve Won't Fall Out	 Automatically Adjusts to Changing Environments No Lost Valves 	
Carry Handle	Hard, One-piece Construction or Thinly Padded with Harder Rubber	Durable Inside Core with Soft Overlay	More Comfortable to Carry	
Nameplate Area	Adhesive Labels	Adhesive LabelsCustom 3-D Logo Option	Easy Customization Permanent, Molded-In Logos That Can't Fall Off	
Cubed Foam System	Single Layer of Cubed Foam	Multilayer Cubed Foam	Highly Customizable to Your Individual Needs	
Panel Mount System	Plastic Frame Screwed to Interior, Variable Height	 Extruded Aluminum Rails with Molded Corner Pieces Watertight, Sealed Rivet Attachment for Custom Fit 	 Stronger Panel Mount Construction Permanent, More Secure Panel Attachment 	

Life is an endurance test—so each Storm Case passes extreme testina requirements.

Test	Specifications Met	Description	
Drop Test	FED-STD-101C, Method 5007.1, Paragraph 6.3, Procedure A, Level A. Tests are superseded and concurrent with ASTM B 4169, DC-18, Assurance Level 1, Schedule A.	A series of 26 drops, one on each corner, edge, and face, from 19" to 30", depending on the gross weight of the case, with loads of 15 lbs to 70 lbs (depending on case size).	
Falling Dart Impact	ATA 300, Category I, "General Requirements for Category I and II Reusable Containers"	A dart weighing 13.22 lbs with a 1.25" hemispherical end was dropped on each case from 19.68".	
Vibration (loose cargo)	FED-STD-101C, Method 5019 Tests are superseded and concurrent with ASTM B 4169, DC-18, Assurance Level 1, Schedule F.	Each case was vibrated for 20 minutes per axis. 1-inch peak to peak at around 4.75 Hz.	
Vibration (sweep)	ATA 300 (Jan 15/96) states in Appendix II, B.4 This test also exceeds the specifications listed in MIL-STD-648C and may also fulfill ISO 8318 and ISO 2247.	Vibration Test for Category I containers — Vibration tests shall be conducted on Category I containers in accordance with ASTM Designation D-999, Procedure B, within the range of 5 to 50 cycles per second for a period of not less than two (2) hours.	
Simulated Rainfall	MIL-STD-810F, Method 506.4, Procedure II of 4.1.2 FED-STD-101C Method 5009.1, Sec 6.7.1 Tests are superseded and concurrent with ASTM B 4169, DC-18, Assurance Level 1, Schedule H.	Four inches of rain per hour for 20 minutes each side. This was followed by a 4-hour test at 4" per hour on the top. Both tests saw the case heated to 18°F higher than the water temp.	
Immersion	MIL-STD-810F, Method 512.4	A 1-meter (3.281 feet) immersion for 1 hour with the case being heated to 40°F higher than the water temperature.	

Storm Cases are more than just watertight, padlockable and **made in the USA**, they're also Guaranteed for Life. Interested in Harnessing the Power of a Storm? Call us at **800.542.7344** or visit us online at **StormCase.com**.



